

Energy Efficient Ventilated Façades for Optimal Adaptability and Heat Exchange enabling low energy architectural concepts for the refurbishment of existing buildings.



E2VENT WORKSHOP

„Think green, think Smart Façade“

LHTES: Latent Heat Thermal Energy Storage System

Dr. Antoine Dugué
Coordinator project E2VENT



Nobatek

BUDMA 2018

The project leading to this application has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 637261 .



Focus on the LHTES




Focus on the LHTES

PCM (Phase Change Materials) to store heat



1. Phase change for temperatures close to T_{int}
 2. To store great amount of energy in a define volume
 3. The building's inertia is increased
- Different types of PCM materials :



	Rubitherm RT21	Rubitherm RT25	Rubitherm RT28
Latent heat (J/kg)	180000	218000	235000
Liquid density (kg/m ³)	770	770	770
Thermal capacity (J/kg/K)	2000	2000	2000
Conductivity (W/m/K)	0.6	0.2	0.2
Melting temperature range (°C)	19-23	22-25	26.5-28.5

LHTES system: concept for cooling



- Two circuits EXT – EXT and INT – INT

LHTES: design



- Use of PCM encapsulated in tubes made of aluminum
- Selection of actuators:
 - Fan
 - Dampers
 - Sensors
- Connection to the Building Energy Management system



LHTES: 1st prototype



- From the manufacturing site to the lab for testings




Talence



Athens



LHTES system: Lab scale testings



$T_{Height; Depth; Position}$ →
 Height = Top (T); Centre (C); Bottom (B)
 Depth = Front (F); Centre (C); Back (B)
 Position = Left (L); Centre (C); Right (R)


View of the LHTES system with tubes

Location of the sensors

Laboratory testings



Evolution of the temperatures




Conclusion:

- 7 hour cycle
- 500 W max (fan = 25 W)
- 2,0 kWh of energy stored while mode gives 2,1 kWh
- COP = 9

Overall:

- In laboratory, quite conclusive

Evolution of the fluxes



... But what about on real site ?


Real scale testings on a test bench



- For the prototype validation. Use of test bench in Anglet, France



Real scale testings on a test bench



- Installation with all partners involved
→ feedback for installation



Conclusion:

- Similar measurements

Pilot site in Burgos



- Installation in Burgos of 2 LHTES.



Pilot site in Burgos



- Waiting for summer for analysis of measurements.





Thank you for your attention.

Contact

Antoine Dugué – Nobatek/INEF4

adugue@nobatek.com

